




Drawings & Terminal Position



Handling and Storage

- Can be mounted or stored in any orientation except inverted
- 2-years storage life at 77°F (25°C) without needing to charge. Recharge when the OCV is <12.2V (50% SOC).
- Classified as non-spillable and approved as non-hazardous cargo for ground, sea and air transportation in accordance with the requirements of IMDG (International Maritime code for Dangerous Goods) and ICAO (International Civil Aviation Organisation)

Charging and Self-Discharge

| Type of charging curve | IUU |
|--|----------------|
| Charger voltage at 68°F (20°C) | 14.4V to 14.8V |
| Self-discharge per month at 68°F (20°C) | 1.25% |
| Self-discharge per month at 104°F (40°C) | 5% |
| 80% depth of discharge cycles | 400 |
| | |

PDF Generated at https://eu.odysseybattery.com 10/13/2023 08:46:04

Information correct at time of exporting PDF. Please check website for updates.

Technical Data Sheet

ODP-AGM31M

(31M-925)

Battery Type

- With SAE posts and 3/8 inch positive and 5/16 inch negative thread SS stud terminals
- Absorbed Glass Mat (AGM) with Thin Plate Pure Lead (TPPL)
- Advanced dual purpose battery for engine start and deep cycle use

Power and Performance

| Voltage | 12V |
|--|---|
| Pulse (5 second) Hot Cranking Amps (PHCA) | 1750A |
| Cold Cranking Amps (CCA) | 925A |
| HCA | 1325A |
| MCA | 1150A |
| 20Hr Nominal Capacity (Ah) | 100Ah |
| 10Hr Nominal Capacity (Ah) | 92Ah |
| Reserve Capacity Minutes | 200 mins |
| Terminal | SAE and 3/8-16" Stud (Pos.), 5/16-18" Stud (Neg.) |
| Torque Spec in-lbs (Nm max) | 200 (22.6)/100 (11.3) studs only |
| Internal Resistance (m Ω) | $2.6~\text{m}\Omega$ |
| Short Circuit (A) | 2600A |

Dimensions and Weight

| Length | 13 in / 330 mm |
|-----------------------------|--------------------|
| Width | 6.8 in / 173 mm |
| Height (terminals included) | 10 in / 254 mm |
| Height (container) | 8.9 in / 226 mm |
| Weight | 69.5 lbs / 31.5 kg |

Temperature

Operating temperature range $-40^{\circ}\text{F}/-40^{\circ}\text{C}$ to $140^{\circ}\text{F}/+60^{\circ}\text{C}$ Optimum storage temperature $68^{\circ}\text{F}/+20^{\circ}\text{C}$

Accreditations

The management systems governing the manufacture of this product are ISO 9001 and ISO 14001 certified.

*Cold Start Performance S.A.E J537 Apr 2016



EnerSys World Headquarters 2366 Bernville Roa

2366 Bernville Road Reading, PA 19605, USA Tel: +1-800-964-2837 EnerSys EMEA EH Europe GmbH Baarerstrasse 18

6300 Zug, Switzerland

EnerSys Asia 152 Beach Road #11-08 Gateway East Building Singapore 189721 Tel: +65 6416 4800 Want more info? Scan code to access the ODYSSEY® Battery Literature Library

